



the closest you'll get to the perfect garage door

SECEURO  **GLIDE™**

INSULATED ROLLER GARAGE DOORS



The SeceuroGlide System

- Vertical opening roller design maximizes drive-through height while saving space both in the garage and on the driveway.
- Double-walled aluminium construction is exceptionally strong yet can easily be repaired.
- Insulated curtain and unique brush draught seal protect against cold and noise.
- Remote control operation and automatic locking deliver the ultimate in convenience.
- Mini transmitter units use state-of-the-art rolling code technology for added security.
- A glazing option is available to allow natural light into the garage.
- Manufactured to ISO 9002 quality standard and backed by a two year warranty for peace of mind.
- Choice of up to seven tough low maintenance finishes.



SeceuroGlide insulated roller garage doors combine the convenience of power operation with the advantage of smooth vertical opening. This allows you to park right up to the door, whilst the pocket size transmitter enables you to open and close the door from inside your car. Meanwhile the tightly coiling curtain creates more space inside your garage to accommodate high top off-road vehicles or people carriers.

Every door is made-to-measure in accordance with ISO 9002 so that it fits your garage perfectly. Manufactured from strong corrosion-resistant aluminium with an insulating core, SeceuroGlide is available in a range of seven stylish colours. These durable factory-coated finishes eliminate the need for painting and ensure that your door continues to look good for years and represents a sound investment for your home. Once installed, SeceuroGlide is very low maintenance and comes complete with a comprehensive 2 year guarantee on all manufactured parts for total peace of mind.

This outstanding, yet attractively priced insulated roller garage door concept has been carefully designed and refined to improve on many of the virtues of both conventional steel roller doors and sectional overhead doors.



Pictured right: SeceuroGlide can easily accommodate curved or arched entrances.

SeceuroGlide

The ultimate in stylish luxury and effective security is at your fingertips with SeceuroGlide insulated roller garage doors. They signal the end of driveway struggles in all weathers and the beginning of peace-of-mind and total convenience from the moment you touch the button and see the door effortlessly rise at your command.

SeceuroGlide is robust, reliable and offers secure protection for your car and home. Aluminium slats lock into position to resist attack by intruders and advanced insulation and brush sealing make the door as weatherproof as it is secure. Vertical opening means you can make maximum use of your drive space and park safely only inches from the door.

The SeceuroSmart control unit uses secure state-of-the-art rolling code technology and allows you to operate and lock the door remotely. During a power failure, SeceuroGlide can be operated manually from inside the garage. An optional external override is also available if required. Where mains power is not available or a budget SeceuroGlide is required, a manual version is available in single door sizes.



SeceuroGlide Compact

Where the headroom inside your garage is particularly limited, a new Compact version of SeceuroGlide is now available which requires only 8" (205mm) above the opening height. Using a 55mm insulated aluminium profile opening widths of up to 3 metres can easily be accommodated.

The SeceuroGlide Compact package includes a neat 90° fascia that completely conceals the back of the door's coil, so drive through height permitting, it can be installed partly or completely into the garage door opening.

SeceuroGlide Compact is also suitable for external applications as all exposed components are made from corrosion resistant aluminium and then powder coated to a high standard.

Where required an optional 45° canopy can be supplied to completely enclose the curtain's coil. These features mean that SeceuroGlide Compact looks and performs just as well when fitted onto the outside of your garage, as it does when fitted on the inside.

- Suits both internal and external applications.
- Only 205mm headroom required.
- Slim 60mm guide rails.
- Low maintenance.
- Fully painted finish.
- Insulated curtain.
- Available in white and brown ONLY.



SeceuroGlide... Better at every stage



Operation

Opening the garage without leaving your car will keep you dry and secure, whilst vertical operation allows you to park right up to the garage door without wasting valuable drive space.



Construction

Achieves maximum drive-through height to accommodate off-readers and people carriers. The individual aluminium slat construction is exceptionally strong yet can be easily repaired if damaged.



Design

SeceuroGlide's roller design frees valuable overhead storage space that is wasted by traditional up-and-over or sectional garage doors. There is no need for keys as it locks automatically when closed.



Insulation

SeceuroGlide's tough double skin curtain is insulated with high density CFC-free foam to reduce heat loss and sound transmission. An innovative brush seal (patent pending) achieves superior draught proofing.

Technical Features



Standard Slat

Vision Slat

Compact Slat

Insulated Curtain

Each curtain is assembled from twin-walled aluminium slats that are insulated with CFC-free foam to reduce heat loss and sound transmission. Glazed vision slats are also available.

Sonfy Power

Sonfy tubular motors are regarded as market leaders and power all electrically operated SecuroGlide®. A manual override facility ensures that all doors can be raised from inside the garage in the event of power loss.



Maximum Safety

All automatic SecuroGlide® doors are equipped with an intelligent safety photocell to stop operation if an obstruction in the path of the door is detected.



Secure Control

SecuroSmart receivers come complete with an integral courtesy light and two mini transmitters with high security rolling codes.

Installation Options

1 Face Fix Installation


Here the inside edge of the guide rails line up with the brick opening. However the flush fitting head plates and flat design of the guide rails make the size of the door and positioning of the guide rail less critical. A subframe is not required unless the structure is very uneven. Moreover, if maximising the width of the opening is not important, an existing subframe can be retained with the door installed in line with the timber opening. If required the guide rails can overlap into the opening by up to 25mm on each side.

2 Reveal Fix - Installation in the Door Opening or Between Walls

If the door is manufactured to the exact opening width, it can be installed within the aperture. This may also depend on the available headroom above to accommodate the coil. If the coil is going to be visible from the outside, an external 90° fascia will be required.

3 Headroom Requirement

The small coil diameter is one of SecuroGlide's strengths. Just 300mm headroom is required inside the garage for doors up to 2500mm opening height and 350mm for doors up to 3500mm opening height. Where the available headroom is severely restricted SecuroGlide Compact requires just 205mm headroom for doors with an opening height up to 2300mm. Alternatively SecuroGlide Compact can be fitted externally. We strongly recommend that a minimum 55mm of bottom slat should hang down into the guide rails when the door is fully raised. Below this is the 'drive through height'.



Choose from seven stylish colours



Please note:

Bottom, vision and locking slats, along with optional powder coated guides may be a slightly different shade to the curtain.
Woodgrain is supplied with brown bottom, vision and locking slats.
SecuroGlide Compact is available in ONLY brown and white and is NOT available with the vision slat option.

WARRANTY: All SecuroGlide products are guaranteed against defect of material or workmanship by SWS UK, subject to correct installation and operation, for a period of 24 months from the date of purchase.

In line with SWS UK's policy of continuous product improvement, we reserve the right to make changes without prior notification. Whilst every effort has been made to provide an accurate representation, colours shown in this brochure are for illustrative purposes only and may vary from the product received.

